Cam Head 120



DESCRIPTION

The Cam display head by Tech Lighting combines minimal design style with high-functionality. This unique display head rotates a full 360° and pivots at 90° allowing for direct light beam in the desired location. The Cam is available in two ontrend finishes and four distinct stem lengths. This low-voltage display head is compatible with a myriad of accessories and systems available by Tech Lighting that further enhances its performance and style. This dynamic display head is ideal for commercial lighting applications such as retail stores, libraries and galleries. The Cam accommodates a fully dimmable MR16 $\,$ lamp (sold separately). Low-voltage, MR16 lamp of up to 75 watts (not included).

INSTALLATION


Socket terminates with FreeJack male connector, which may be installed into a system connector. Elements ordered with a system prefix include a connector for that system. For use on T~TRAK, order FreeJack version and T~TRAK FreeJack Connector (sold separately).

WEIGHT

0.26-0.86lb / 0.12-0.39kg ±



cam head



ORDERING INFORMATION

700 SYSTEM CAM	LENGTH (A)	FINISH
FJ FREEJACK	03 3"	C CHROME
MP MONOPOINT	06 6"	S SATIN NICKEL
MO MONORAII	12 12"	

Note: MP includes 4" Round Flush Canopy.

MO2 TWO-CIRCUIT MONORAIL



7400 Linder Avenue Skokie, Illinois 60077 T 847.410.4400 F 847.410.4500

Tech Lighting, L.L.C.

700 CAM
FIXTURE TYPE:
JOB NAME:
NOTES:



©2019 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.