


# LOW - VOLTAGE HEADS

## K-Rae Head LED T20

### DESCRIPTION

More than just a head, this unique fixture integrates the uncompromising light quality of our Unilume LED Micro Channel (which utilizes remote phosphor LED technology) with the versatility of Kable Lite. Available in two parallel length options and one perpendicular length option (consult factory for custom lengths). Each head pivots 360° and can be mounted up or down for easy control of light making it ideal for direct and indirect general illumination, wall wash and display applications. When used in conjunction with other low-voltage heads and pendants, the K-Rae offers incredible flexibility to layer light throughout a space 8 watts/ft, 570 net lumens/ft.



### WEIGHT

0.19-0.75lb / 0.09-0.34kg ±



k-rae head

### ORDERING INFORMATION

700KLRAER	CRI	COLOR TEMP	LENGTH (A)	CABLE SEPARATION	FINISH	LAMP
8	80 CRI	24 2400K	05 5"	05 5.5"	S SATIN NICKEL	-LED LED
9	90 CRI	830 80 CRI 3000K	12 12"			
		835 80 CRI 3500K	24 24"			
		840 80 CRI 4000K				
		930 90 CRI 3000K				



**TECH LIGHTING®**

7400 Linder Avenue T 847.410.4400  
Skokie, Illinois 60077 F 847.410.4500

Tech Lighting, L.L.C.

700KLRAER \_\_\_\_\_

FIXTURE TYPE: \_\_\_\_\_

JOB NAME: \_\_\_\_\_

NOTES: \_\_\_\_\_

\_\_\_\_\_

\_\_\_\_\_

