

PRODUCT FEATURES

- Ultra-contemporary minimalist design style
- Features two contemporary color options, Satin Nickel and White
- Complementary 17 inch and 20 inch size options available
- Ideal for bathrooms, hallways and closets
- Fully dimmable LED lamping option creates the desired ambiance in your unique space
- Protected by a 5-year warranty with integrated LED



LAMPING

LED includes 32 watt 658.2 delivered lumen, 90 CRI, 3000K LED module. Dimmable with most LED compatible ELV and Triac dimmers. ADA compliant. Can be mounted on wall or ceiling.

Silver



Silver

White

ORDERING INFORMATION

700FMC RST SHAPE OR SIZE	FINISH	LAMP
12 12	W MATTE WHITE S SATIN NICKEL	-LED930 INTEGRATED LED 90 CRI 3000K 120V -LED930-277 INTEGRATED LED 90 CRI 3000K 277V

700FMC RST _____

JOB NAME _____


NOTES _____



CREST 12 CEILING

SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	3 lbs
HEIGHT	1.8in
WIDTH	12.3in
LENGTH	12.3in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
WALL / CEILING MOUNT	
GENERAL LISTING	
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS		658.2		
WATTS		32		
MAX WATTAGE PER BULB		32W		
INPUT VOLTAGE		120V 277V		
DIMMING TYPE*		ELV, TRIAC 0-10V		
CCT		3000K		
CRI		90 CRI		
LED LIFETIME				
L70				
AVERAGE BULB HOURS		50000		
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		T3		
LAMP INCLUDED?		Y		
WARRANTY**		5 Years		

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

