

KABLE LITE MINI SURFACE ELECTRONIC TRANSFORMER

PRODUCT FEATURES

LAMPING

Constructed of die-cast aluminum and can power lamps totaling up to 300 watts. The transformer is concealed inside a decorative housing and features fast acting secondary short circuit and overload protection that will safely turn the system off should a short occur. Once the short has been removed, the unit can be reset by simply flipping the wall switch off and on. Mounts to a standard 4" ceiling junction box with round plaster ring (provided by electrician). Each cable lead is 4 feet in length.



Kable Lite Mini Surface Electronic Transformer



Kable Lite Mini Surface Electronic Transformer

ORDERING INFORMATION

700KLMRT250F FINISH

S-LED SATIN NICKEL

700KLMRT250F _____

JOB NAME _____


NOTES _____



KABLE LITE MINI SURFACE ELECTRONIC TRANSFORMER

SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	2.75 lbs
HEIGHT	1.4in
WIDTH	5.3in
LENGTH	5.3in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB			250W	
INPUT VOLTAGE			120V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Y	
WARRANTY**				

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

