

PRODUCT FEATURES

- High-tech display head that combines simplicity with practical technology
- Telephoto camera lens inspired design
- Highly customizable featuring a plethora of finishes, beam spreads, lamping and stem lengths
- Compatible with the free-jack or rail system also available by Tech Lighting
- Pivots 88° and able to point straight down
- Protected by a 5-year warranty



LAMPING

Includes field replaceable 14.2 watt, 634 delivered lumen, 2700K, 3000K or 3500K field replaceable LED module. Dimmable with most LED compatible ELV or Triac dimmers. Choice of 18° or 40° field changeable optics. Integrated lens holder accommodates up to two MR16 sized lenses or louvers (sold separately). As a general rule when using the Burk head, we do not recommend using greater than 70% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.

Aged Brass /
Aged Brass



Antique Bronze /
Antique Bronze

Black /
Satin Nickel

Satin Nickel /
Satin Nickel

White /
Satin Nickel

To view all available finish options, please visit techlighting.com

ORDERING INFORMATION

700	SYSTEM	BRK	CRI	COLOR TEMP	BEAM SPREAD	LENGTH (A)	FINISH	LAMP
	FJ FREEJACK	8	80 CRI	27 2700K	20 18°	03 3"	R AGED BRASS	LED
	MP MONOPOINT	9	90 CRI	30 3000K	35 40°	06 6"	Z ANTIQUE BRONZE	
	MO MONORAIL			35 3500K			B BLACK	
							S SATIN NICKEL	
							W WHITE	

Compatible with following accessories. 140MR16DF DIFFUSOR LENS MR16/PAR16 *** 140MR16LL LINEAR SPREAD LENS MR16/PAR16 *** 140MR16SB SANDBLASTED LENS MR16 *** 140MR16SF SOFT FOCUS LENS MR16/PAR16 *** 700A02-BK EGGRATE MR16/PAR16 BLACK

700 _____ BRK _____

JOB NAME _____


NOTES _____



BURK HEAD

SPECIFICATIONS

PRIMARY MATERIAL	Metal
SHADE MATERIAL	
NET WEIGHT	2 lbs
HEIGHT	3in
WIDTH	3.6in
LENGTH	3in
BEAM SPREAD	
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	
DRY LISTED	
MIN. HANGING HEIGHT	3in
MAX HANGING HEIGHT	3in
TOTAL CORD LENGTH	
SLOPED CEILING ADAPTABLE?	N/A
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	634.0			
WATTS	14.2			
MAX WATTAGE PER BULB	14.2W			
INPUT VOLTAGE/ DIMMING TYPE	12V ELV, MLV 120V ELV, MLV			
CCT	2700K 3000K 3500K			
CRI	80 CRI 90 CRI			
LED LIFETIME				
L70	>50000			
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED			
LAMP SHAPE	Integrated LED			
LAMP INCLUDED?	True			
WARRANTY**	5 Years			

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.		No	
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		N/A	

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

