

## PRODUCT FEATURES

Remote Lutron Hi-lume Power Supply for EcoSystem compatibility with dimming down to 0.1%. Universal input 120V-277V with 24V DC output available in 100W. Enclosure included.



## LAMPING

Closed



Closed

Open

## ORDERING INFORMATION

ESPR	WATTAGE	OUTPUT VOLTAGE	CONTROLS	INPUT VOLTAGE
	100 100W	24 24VDC	HLECO HI-LUME 3 WIRE/ECO-SYSTEM	120-277 120-277V

ESPR \_\_\_\_\_

JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_

\_\_\_\_\_



# LUTRON HI-LUME ECOSYSTEM/3-WIRE 0.1%



## SPECIFICATIONS



PRIMARY MATERIAL
SHADE MATERIAL
NET WEIGHT
HEIGHT
WIDTH
LENGTH
WET LISTED
DAMP LISTED
DRY LISTED
GENERAL LISTING
INCLUDES

## LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE/ DIMMING TYPE				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?				
WARRANTY**				

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)  
 \*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 <b>Title 24</b> Part 6 / JA8.			Yes
This product can be used to comply with California Appliance Efficiency Standards 2016 <b>Title 20</b> and may be shipped to and sold in California.			Yes

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

