

KABLE LITE 4" ROUND POWER FEED CANOPY DUAL-FEED



PRODUCT FEATURES

LAMPING

It can be used anywhere in the run. It brings power to the Kable Lite run from a remote dual-feed transformer (sold separately). The low-voltage leads from the remote transformer are connected to the canopy leads inside a standard 4" junction box. The four leads from the canopy are 24" long and can be cut and bent in the field. To drop the Kable Lite system farther down from the ceiling, add two pair of hardwire feeds (sold separately). Isolating connectors for bare cable are included to isolate power feeds from each other.



Kable Lite 4" Round Power Feed Canopy Dual-Feed



Kable Lite 4" Round Power Feed Canopy Dual-Feed

ORDERING INFORMATION

700KP4C424 SHAPE OR SIZE	LENGTH (A)	FINISH
4" ROUND	24"	S SATIN NICKEL

700KP4C424 _____

JOB NAME _____


NOTES _____



KABLE LITE 4" ROUND POWER FEED CANOPY DUAL-FEED

SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	0.8 lbs
HEIGHT	24in
WIDTH	2.5in
LENGTH	3.6in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB				
INPUT VOLTAGE			0V	
DIMMING TYPE*				
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Y	
WARRANTY**			1 Year	

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

