

PRODUCT FEATURES



LAMPING

Vaulted version available for ceilings up to 45°. Electronic transformer inside 2" high, 4.5" diameter housing. One FreeJack port. for ceiling or wall.

FreeJack Surface Canopy LED



FreeJack Surface Canopy LED

ORDERING INFORMATION

700FJSF	SHAPE OR SIZE	FINISH	VOLTAGE
4	4" ROUND SURFACE INTEGRAL TRANSFORMER	Z ANTIQUE BRONZE	-LED 120V IN/12V OUT LED
4V	4" ROUND SURFACE VAULTED INTEGRAL TRANSFORMER	NB NATURAL BRASS	-LED277 277V IN/12V OUT LED
		BK NIGHTSHADE BLACK	
		S SATIN NICKEL	

700FJSF

JOB NAME

NOTES




FREEJACK SURFACE CANOPY LED



SPECIFICATIONS

HARDWARE MATERIAL	
SHADE MATERIAL	
NET WEIGHT	1 lbs
HEIGHT	2.3in
WIDTH	4.5in
LENGTH	4.5in
WET LISTED	
DAMP LISTED	
DRY LISTED	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS				
WATTS				
MAX WATTAGE PER BULB			60W	
INPUT VOLTAGE			120V 277V	
DIMMING TYPE*			ELV	
CCT				
CRI				
LED LIFETIME				
L70				
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE				
LAMP SHAPE				
LAMP INCLUDED?			Y	
WARRANTY**			5 Years	

* Dimming information available at www.techlighting.com/Downloads#dimming

** Visit techlighting.com for specific warranty limitations and details.

T20 / T24 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6.			N/A
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.			N/A

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

