

Unilume LED Slimline					
MANUFACTURER	DIMMER TYPE	PART NUMBER	FIXTURES PER DIMMER	MEASURED LIGHTING OUTPUT RANGE	COMMENTS
Leviton	ELV	6615	2-25*	95%-30%	Low-level flickering, can be corrected with dimmer adjustment.
Lutron	Incandescent	DV-600P-WH	1-6*	98%-6%	
Lutron	LED	DVCL-153P-WH	1-42*	97%-20%	Some humming noise
Lutron	ELV	DVELV-303P	1-42*	98%-6%	
Leviton	ELV	IPE04	2-25*	98%-22%	
Lutron	Incandescent	MA-600-WH	1-6*	99%-20%	Delayed start
Lutron	ELV	MRF2-6ELV-120-WH	1-42*	97%-1%	
Lutron	ELV	NTELV-600-WH	1-42*	98%-10%	
Lutron	ELV	NVELV-600-WH	1-42*	98%-12%	
Lutron	ELV	SELV-600-WH	1-42*	95%-6%	
Leviton	ELV	VPE04	2-25*	98%-25%	
Leviton	ELV	VRE06	2-25*	98%-8%	
*Can vary based on fixture length combination, totals reflect all 19" lengths. *All 7" Fixtures must be dimmed with at least one other fixture for proper dimming results. *Recommend derating incandescent dimmers by 90% and ELV dimmers by 30%.					